

acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Revision: 2019-06-14 Replaces version of: 2018-05-25 (GHS 1)

SECTION 1: Identification

1.1 Product identifier

Trade name Medallion VOC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Metal polish

1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States

Telephone: 1.800.875.6320, 1.303.289.6320

e-mail: info@bbblending.com Website: bbblending.com

e-mail (competent person) btirrell@bbblending.com

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500

24 hr emergency information

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

United States: en Page: 1 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Revision: 2019-06-14 Replaces version of: 2018-05-25 (GHS 1)

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.
P321 Specific treatment (see on this label).

P362 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

142 Solvent

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
142 Solvent	CAS No 64742-47-8	20-<40	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 4 / H227	

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first- aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

United States: en Page: 2 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Replaces version of: 2018-05-25 (GHS 1) Revision: 2019-06-14

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

United States: en Page: 3 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Revision: 2019-06-14 Replaces version of: 2018-05-25 (GHS 1)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Occupational exposure limit values (Workplace Exposure Limits)

Control of the effects

Protect against external exposure, such as

Frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	alpha-Alumina	1344-28- 1	REL							appx- D	NIOS H REL
US	alpha-alumina	1344-28- 1	PEL		15					i, dust	29 CFR 1910.1 000
US	alpha-alumina	1344-28- 1	PEL		5					r, dust	29 CFR 1910.1 000
US	aluminium oxide	1344-28- 1	PEL (CA)		10					dust	Cal/ OSHA

5

PEL

Cal/ OSHA

PEL

Notation

US

appx-D see Appendix D - Substances with No Established RELs

1344-28-

1

PFI

(CA)

Ceiling-C ceiling value is a limit value above which exposure should not occur dust as dust

i inhalable fraction r respirable fraction

aluminium oxide

United States: en Page: 4 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Revision: 2019-06-14 Replaces version of: 2018-05-25 (GHS 1)

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless

TWA otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted

average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)	
Color	light blue	
Odor	characteristic	

Other safety parameters

pH (value)	7.5 – 8.5 (25 °C)	
Melting point/freezing point	not determined	
Initial boiling point and boiling range	100 °C	
Flash point	99 °C at 101.3 kPa 211 °F at 1 atm	
Evaporation rate	not determined	
Flammability (solid, gas)	not relevant, (fluid)	

United States: en Page: 5 / 11





acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Replaces version of: 2018-05-25 (GHS 1)

Explosive limits

not determined

Vapor pressure

3.7 kPa at 37.8 °C

Density

1.11 ^g/_{cm³} at 25 °C

Vapor density

this information is not available

Solubility(ies)

not determined

Revision: 2019-06-14

Partition coefficient

- n-octanol/water (log KOW)	this information is not available	
Auto-ignition temperature	not determined	

Viscosity

Oxidizing properties	none
Explosive properties	none
- Dynamic viscosity	666 cP
- Kinematic viscosity	600 cSt at 25 °C

9.2 Other information there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

United States: en Page: 6 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Revision: 2019-06-14 Replaces version of: 2018-05-25 (GHS 1)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture Exposure Name of substance CAS No **Endpoint** Value **Species** . time 142 Solvent 64742-47-8 LL50 $5 \frac{mg}{l}$ fish 96 h 142 Solvent 64742-47-8 EL50 1.4 mg/_I 48 h aquatic invertebrates

United States: en Page: 7 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Replaces version of: 2018-05-25 (GHS 1) Revision: 2019-06-14

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
142 Solvent	64742-47-8	LL50	17 ^{mg} / _I	fish	24 h
142 Solvent	64742-47-8	EL50	4.6 ^{mg} / _I	aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not assigned
14.2	UN proper shipping name	not assigned
14.3	Transport hazard class(es)	not assigned
14.4	Packing group	not assigned

14.5 Environmental hazards hazardous to the aquatic environment

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

United States: en Page: 8 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Replaces version of: 2018-05-25 (GHS 1) Revision: 2019-06-14

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

not assigned

International Maritime Dangerous Goods Code (IMDG)

not assigned

International Civil Aviation Organization (ICAO-IATA/DGR)

not assigned

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

15.1.5 Toxic Substance Control Act (TSCA)

all ingredients are listed

0.1

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

15.1.5 California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and 0.6 Toxic Enforcement Act of 1987

Proposition 65 List of chemicals	
	Ī

Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
ethanol (ethyl alcohol)	64-17-5	0.0534 wt%	in alcoholic beverages	developmental
methyl isobutyl ketone	108-10-1	0.0006 wt%		cancer
methyl isobutyl ketone (MIBK)	108-10-1	0.0006 wt%		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

 $\label{thm:local_equation} \mbox{ Hazardous Materials Identification System. American Coatings Association.}$

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazard
Health: health hazard

Personal protection: personal protective equipment (PPE) for normal use

United States: en Page: 9 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Version number: GHS 2.1 Revision: 2019-06-14 Replaces version of: 2018-05-25 (GHS 1)

Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Asp. Tox.	Aspiration hazard
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)

United States: en Page: 10 / 11



acc. to 29 CFR 1910.1200 App D

Medallion VOC

Revision: 2019-06-14

Version number: GHS 2.1 Replaces version of: 2018-05-25 (GHS 1)

> Abbr. Descriptions of used abbreviations **ICAO** International Civil Aviation Organization **IMDG** International Maritime Dangerous Goods Code **MARPOL** International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant") NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition Occupational Safety and Health Administration (United States) **OSHA** PBT Persistent, Bioaccumulative and Toxic PFI Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure **TWA** Time-weighted average vPvB Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 11 / 11